

器具・継手類・弁類の直管換算長

呼び径 [mm]	サドル付分水栓	止水栓	メーターユニット (メーターを含む)	メーター	丙水栓 (逆止弁付)	単式逆止弁	エルボ90°	エルボ45°	Ｔ字管(分流)	Ｔ字管(直流)	異径接合	定水位弁 (アングル型)	定水位弁 (ストレート型)
13	2.1	0.12	15.3	2.5	1.5	1.5	0.6	0.36	0.9	0.18	0.2	-	-
20	3.1	0.15	22.1	5.6	10.1	3.1	0.75	0.45	1.2	0.24	0.2	5.8	8.8
25	7.3	0.18	32.5	9.3	12.6	3.3	0.9	0.54	1.5	0.27	0.5	8.1	9.2
30	3.2	0.24	25.2	9.3	10.4	5.5	1.2	0.72	1.8	0.36	1.1	10.5	11.9
40	4.7	0.3	35.7	12	12.7	7.1	1.5	0.9	2.1	0.45	1.1	12.2	13.8
50	6.3	0.39	48.4	21.4	16.9	7.8	2.1	1.2	3	0.6	1.7	15.5	17.6
65	-	0.48	-	-	-	3.6	2.4	1.5	3.6	0.75	-	19.8	22.6
75	-	0.63	-	1.2	-	2.3	3	1.8	4.5	0.9	5	23.7	26.9
100	-	0.81	-	1.7	-	3.7	4.2	2.4	6.3	1.2	5	30.8	35.1
125	-	0.99	-	-	-	4.6	5.1	3	7.5	1.5	-	-	-
150	-	1.2	-	2.7	-	5.4	6	3.6	9	1.8	5	45.6	51.7
200	-	1.4	-	3.8	-	7.6	6.5	3.7	14	4	5	60.8	68.2
250	-	1.7	-	4.9	-	9.8	8	4.2	20	5	5	74.8	84.2

(m)