

器具・継手類・弁類の直管換算長

呼び径「mm」	サドル付分水栓	止水栓	メーターユニット (メーターを含む)	メーター	丙水栓 (逆止弁付)	単式逆止弁	エルボ90°	エルボ45°	Ｔ字管(分流)	Ｔ字管(直流)	異径接合	定水位弁 (アングル型)	定水位弁 (ストレート型)
13	2.1	0.12	22.7	2.5	10.1	1.5	0.6	0.36	0.9	0.18	0.5		
20	3.1	0.15	22.1	5.6	10.1	3.1	0.75	0.45	1.2	0.24	0.5	5.8	8.8
25	7.3	0.18	32.5	9.3	12.6	3.3	0.9	0.54	1.5	0.27	0.5	8.1	9.2
30	3.2	0.24	25.2	9.3	10.4	5.5	1.2	0.72	1.8	0.36	1	10.5	11.9
40	4.7	0.3	35.7	12	12.7	7.1	1.5	0.9	2.1	0.45	1	12.2	13.8
50	6.3	0.39	48.4	21.4	16.9	7.8	2.1	1.2	3	0.6	1.5	15.5	17.6
65		0.48					2.4	1.5	3.6	0.75		19.8	22.6
75		0.63		8.2			3	1.8	4.5	0.9	2	23.7	26.9
100		0.81		11.5			4.2	2.4	6.3	1.2	3	30.8	35.1
125		0.99					5.1	3	7.5	1.5			
150		1.2		18.4			6	3.6	9	1.8	5	45.6	51.7
200		1.4		25.7			6.5	3.7	14	4		60.8	68.2
250		1.7		33.4			8	4.2	20	5		74.8	84.2

(m)